



Genuine Quality.
Durable Trust.



Engine Oil

SAE 15W-40

9.58076

1. PRODUCT IDENTIFICATION

Product:	Motor Oil
Company Identification:	SAC DT1 SAE 15W40
Product Use:	Heavy Duty Engine Oil

2. COMPOSITION

Chemical Composition :	Premium quality mineral oil with additives.
Hazardous Components :	No component is present at sufficient concentration to require hazardous classification.

3. HAZARDS IDENTIFICATION

Hazards :	This material is not considered to be hazardous but should be handled in accordance with good industrial hygiene and safety practices.
-----------	--

4. FIRST AID MEASURES

Eye Contact:	Flush eyes thoroughly with water. Obtain medical advice if any irritation occurs.
Skin Contact:	Wash skin thoroughly with soap and water as soon as reasonably practicable. Remove heavily contaminated clothing and wash underlying skin thoroughly. If irritation persists obtain medical attention.
Ingestion:	Not expected to be a problem. If large quantities of this product are ingested obtain medical advice. DO NOT induce vomiting unless directed so by medical personnel. Never give anything by mouth to an unconscious person.
Inhalation:	Avoid excessive inhalation of mists, fumes or vapour. This causes irritation to the nose and throat, and coughing. Remove person from exposure. If symptoms persist obtain medical advice.

Shop 24/7 here:
partnerportal.dieseltechnik.com





Genuine Quality.
Durable Trust.

5. FIRE FIGHTING MEASURES

Extinguishing media:	In case of fire use water sprays, fog or standard foam is recommended. DO NOT USE water jets. Water may be used to cool nearby heat exposed areas /objects. Avoid spraying directly into storage containers because of the danger of boil-over. Move container away from fire area if you can do it without risk.
Special hazards:	Fires in confined areas should be dealt with by trained personnel wearing approved breathing apparatus. Toxic fumes may be evolved on burning or exposure to heat.
Protective clothing :	Use suitable protective breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Any spillages should be regarded as a potential fire risk. In the event of spillage, remove all sources of ignition and ensure good ventilation. Spilled material may make surface slippery. Clean up spilled material immediately. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated.
Environmental precautions:	Do not wash product into drainage systems, protect drains from potential spills to minimize contamination. In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover from the surface. Protect environmentally sensitive areas and water supplies. Minimize contact of spilled material with soil to prevent runoff to surface waterways.
Small Spills:	For small spills clean up the material immediately. Contain and recover spilled material using sand or other suitable inert absorbent material.
Large Spills:	Recovery of large spills should be affected by specialised personnel.

7. HANDLING AND STORAGE

Handling precautions:	Avoid contact with skin and observe good personal hygiene. Avoid contact with eyes. If splashing is likely to occur wear a full-face visor or chemical goggles as appropriate. Avoid frequent or prolonged skin contact with fresh or used product. Wash hands thoroughly after contact. Use disposable cloths and discard when soiled. Do not put soiled cloths in pockets. Take necessary precautions against accidental spillage into soil and water. Good working practices, high standards of personal hygiene and plant cleanliness must be maintained at all times.
Storage precautions:	Store under cover away from heat and sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:	There is no appropriate occupational exposure limit to this material.
Engineering controls:	The control measures appropriate for a particular worksite depend on how this material is used and on the extent of exposure. If vapour, mists or fumes are generated, their concentration in the workplace air should be controlled to the lowest reasonably practicable level.

Shop 24/7 here:
partnerportal.dieseltechnic.com





Genuine Quality.
Durable Trust.

Personal Protective Equipment
Respiratory system:

Respiratory protection is unnecessary, provided the concentration of vapour, mists or fumes is adequately controlled. The use of respiratory equipment must be strictly in accordance with any statutory requirements governing its selection and use.

Hands:
Eyes:

Use chemical resistant, impervious gloves.

Safety glasses with side shields. Goggles with a face shield may be necessary depending on conditions of use.

Skin:

Disposable outer garments where there is the potential for contact with the material.

9. TYPICAL PROPERTIES

Properties	Unit	Typical	ASTM TEST
Viscosity at 40°C	mm ³ /s	110	D445
Viscosity at 40°C	mm ³ /s	14.5	D445
Viscosity Index	VI	130	D2270
Total Base Number	mg KOH/g	10.7	D2896
Density	°C	0.886	D4052
Flash Point	°C	210	D92
Pour Point	°C	-29	D97

10. STABILITY AND REACTIVITY

Conditions to avoid:

Sources of ignition. Thermal decomposition products will vary with conditions. Incomplete combustion will generate smoke, carbon dioxide and hazardous gasses, including carbon monoxide.

Incompatible Materials:

Avoid contact with strong oxidizing agents.

Stability:

Stable at ambient temperatures. Hazardous polymerization reactions will not occur.

11. TOXICOLOGICAL INFORMATION

Skin contact:

Unlikely to cause harm to the skin on brief or occasional contact.

Eye contact:

Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

Ingestion:

Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.

Inhalation:

At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May cause irritation to eyes, nose and throat due to vapour, mists or fumes. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occur.

Shop 24/7 here:

partnerportal.dieseltechnic.com





Genuine Quality.
Durable Trust.

12. ECOLOGICAL INFORMATION

Aquatic toxicity :	Spills may form a film on water surfaces causing physical damage to organisms; oxygen transfer could also be impaired.
Biodegradability:	This product is inherently biodegradable.
Bioaccumulation:	There is no evidence to suggest bio-accumulation will occur.
Mobility:	Spillages may penetrate the soil causing ground and water contamination.

13. DISPOSAL CONSIDERATIONS

Disposal Methods:	Where possible, arrange for the product to be recycled. Dispose via an authorized person / licensed waste disposal conductor in accordance with local regulations.
-------------------	--

14. TRANSPORT INFORMATION

Road Transport:	Not classified as hazardous for transport
-----------------	---

15. REGULATORY INFORMATION

EEC hazard classification:	Not classified
----------------------------	----------------

16. OTHER INFORMATION:

This data sheet and health, safety and environmental information it contains are considered to be accurate as of the date specified below. We have reviewed any information contained herein which we received from sources outside Diesel Technic and/or its distributor SAC Commercial Parts. However, no warranty or representation, express or implied is made as to the accuracy or completeness of the data and information contained in this data sheet. Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid license. Diesel Technic and/or its distributor SAC Commercial Parts shall not be held responsible for any damage or injury resulting from abnormal use of material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.

Shop 24/7 here:
partnerportal.dieseltechnic.com

