



Genuine Quality.  
Durable Trust.



# Engine oil

## SAE 10W-40 UHPD

### 9.58072

DT Spare Parts Engine Oil 9.58072 is a universal, high-performance engine oil for diesel engines with and without turbochargers, particularly suitable for EURO 4 and EURO 5 commercial vehicle engines.

It guarantees a very good performance and enables the longest oil-change intervals in accordance with the recommendations of the vehicle manufacturer based on the following quality criteria:

- » Easy, low-wear cold-start as a result of good flow fluidity, even at low temperatures
- » Distinguished ageing and corrosion protection
- » Extraordinary wear protection and detergency
- » Excellent thermal oxidation stability and low vaporisation inclination

#### Specifications:

- ACEA E4 / E7
- MAN M 3277
- API CI-4 + UHPD
- MAN M 3377
- Caterpillar ECF 1-a, ECF 2
- MB 228.5
- Cummins CES 20076, 20077, 20078
- MTU Typ 3
- Deutz DQC IV-10
- Renault RXD, VI RLD-2
- Global DHD-1
- Scania LDF-3
- Iveco (wenn für ACEA E4-/E7-08 empfohlen)
- VOLVO VDS-3
- MACK EO-M+

| Properties                     | Method | Unit               |            |
|--------------------------------|--------|--------------------|------------|
| Density, 15 °C                 | D 4052 | g/ml               | 0.869      |
| Viscosity Grade                | -      | -                  | SAE 10W-40 |
| Kinematic Viscosity, 40 °C     | D 445  | mm <sup>2</sup> /s | 100        |
| Kinematic Viscosity, 100 °C    | D 445  | mm <sup>2</sup> /s | 15         |
| Viscosity Index                | D 2270 | -                  | 157        |
| Total Base Number              | D 2896 | mg KOH/g           | 12.5       |
| Pour Point                     | D 97   | °C                 | -39        |
| Flash Point, COC               | D 92   | °C                 | 230        |
| Sulfated Ash                   | D 874  | % mass             | 2.0        |
| Borderline Pumping Temperature | D 3829 | °C                 | -27        |

The figures above are not specifications. They are typical figures obtained within production tolerances.

Shop 24/7 here:  
[partnerportal.dieseltechnic.com](https://partnerportal.dieseltechnic.com)

